

# VIAFLEX TAPE

## Asphaltic waterproof tape lined with flexible aluminum

### DESCRIPTION

Viaflex Tape is a self-adhesive waterproof tape composed of one layer of asphaltic adhesive lined with flexible aluminum sheeting and protected with a removable plastic covering. It is an easy-to-use tape that provides rapid solutions for repairs, leaks and seepage.

### ADVANTAGES

- Easy, fast application;
- Impermeable and water-resistant;
- Good resistance to direct sunlight;
- Flexible;
- Adheres easily to the majority of surfaces encountered in civil engineering, such as concrete, mortar, bricks, tiles, aluminum, etc;
- Can be applied with special tools

### UTILIZATION

- Roofing tiles (metallic, asbestos-cement and concrete)
- Flashings and metallic troughs/gutters.
- As protection on PVC tubing exposed to weather.
- Ventilation and air-conditioning ducts.
- **Cantoneiras**, cargo vans, bodywork of closed cargo compartments on trucks.
- Camping tents.
- Sealing overlaps in under-roofing systems

### USAGE INSTRUCTIONS

Start by removing loose pieces and other fragments/litter. Remove the plastic film covering the adhesive face of the **Viaflex Tape** and apply the tape firmly over the area in need of repair, using greater force on the edges.

In the case of porous surfaces, we recommend that the surface first be primed with **Viabit** or **Adeflex** bituminous paint or **Ecoprimer** primer and allowed to dry for a minimum of 6 hours.

**Viaflex Tape** is not recommended for surfaces subject to high temperatures.

For better performance, **Viaflex Tape** should be applied when room temperature is above 20°C

### USAGE RESTRICTIONS

- Do not use as a substitute for metallic flashings.
- Do not use on surfaces subject to high temperatures, like internal areas of a barbecue pit. Do not apply in cold or rainy weather or on moist substrate

## PACKAGING / STACKING

Width	Length	Total area
0.05 m	10 m	0.5 m <sup>2</sup>
0.10 m	10 m	1.0 m <sup>2</sup>
0.15 m	10 m	1.5 m <sup>2</sup>
0.20 m	10 m	2.0 m <sup>2</sup>
0.30 m	10 m	3.0 m <sup>2</sup>
0.45 m	10 m	4.5 m <sup>2</sup>
0.94 m	10 m	9.4 m <sup>2</sup>

## VALIDITY / STORAGE

2 (two) years from date of manufacture, in original intact packaging, in a covered, dry, ventilated location, far from sources of heat.

## SAFETY RECOMMENDATIONS

Prior to starting work consult the SSCP (Safety Information Sheet for Chemical Products) of the products, available on our site: [www.viapol.com.br](http://www.viapol.com.br)

Use adequate PPE, such as gloves, facial protection mask, waterproof boots and safety eyewear. Keep the product out of the reach of children and domestic animals.

In case of contact with the skin, wash the area with neutral soap and water.

In case of contact with the eyes, wash copiously with potable water for a minimum of 15 minutes and seek medical assistance.

In the eventuality of irritation of the skin, eyes or ingestion of the product, seek medical assistance, citing the type of product involved.

In case of ingestion, do not induce vomiting and seek medical assistance immediately.

## ENVIRONMENTAL PRECAUTIONS

Do not discard materials or residues carelessly. Materials must be disposed of in an appropriate location in accordance with regulations based on local environmental legislation in force, respecting regulations applicable to the characteristics of certain products or materials.

For further details consult the safety sheets (SSCP) of products cited in our site [www.viapol.com.br](http://www.viapol.com.br)

*Note: The information contained in this datasheet is based on our best knowledge and is provided for your help and guidance. We need to point out that the performance of our products depends on the preparation condition of the surface and the storage and application of the product, factors not subject to our control. The consumption of the products in practice depends on the application technique, the condition of the equipment used, and the surface to be coated. We do not, therefore, accept any responsibility of any nature regarding the consumption and performance of our products arising from inadequate storage or use of the products. For further clarification please consult our Technical Department.*

*Viapol reserves the right to alter the specifications and/or information contained in this datasheet without prior notice.*