1 /2



# Viaflex Tape

Asphalt membrane covered with flexible aluminum.

## 1. Description

Viaflex Tape is a self-adhesive waterproof tape composed of a layer of adhesive asphalt, covered with a flexible aluminum sheet and protected by a plastic film. Easy-to-apply material that provides an immediate solution for repairs, leaks and infiltrations.

### 2. Advantages

- Quick and easy application.
- Waterproof and water-resistant.
- Good resistance to sunlight.
- Flexible.
- Adhesion to most materials used in civil construction, such as concrete, mortar, bricks, tiles, aluminum, etc.
- No special tools required for application.

#### 3. Use

- Tiles (metallic: fiber cement and concrete);
- Metal flashes and gutters;
- Protection of PVC piping exposed to the weather;
- Ventilation and air conditioning ducts;
- Corners, vans, box bodies;
- Camping tent;
- Closing of overlaps in undercover system.

## 4. Instructions For Use

Start by removing loose parts and impurities from the surface. Remove the plastic film from the adhesive side of Viaflex Tape and apply it firmly, with special attention to the edges.

For porous surfaces, it is recommended to prime it with Viabit, Adeflex or Ecoprimer bituminous paint and allow it to dry for at least 6 hours. Proceed with placing the Viaflex Tape normally.

Viaflex Tape is not indicated for surfaces subject to high temperatures.

For best performance, Viaflex Tape must be applied when the ambient temperature is above 20°.

#### 5. Use Restrictions

- Do not use as a replacement for metal flashings.
- Areas subject to high temperatures such as internal barbecue areas;
- Do not apply in cold, rainy weather or wet substrate;



## 6. Presentations

Width	Length	Total Area
0,05 m	10 m	0,5 m²
0,10 m	10 m	1,0 m <sup>2</sup>
0,15 m	10 m	1,5 m²
0,20 m	10 m	2,0 m <sup>2</sup>
0,30 m	10 m	3.0 m <sup>2</sup>
0,45 m	10 m	4.5 m <sup>2</sup>
0,94 m	10 m	9.4 m <sup>2</sup>

#### 7. Expiration date/Storage

02 (two) years from the date of manufacture in original and intact packaging, in a covered, dry, ventilated place and away from heat sources.

## 8. Security Recommendations

Before starting to handle the product, consult the Chemical Product Safety Information Sheet, available on our home page www.viapol.com.br

Use appropriate PPE such as gloves and face protection mask, waterproof boots and safety glasses. Keep the product out of the reach of children and pets.

In case of contact with the skin, wash the area with water and neutral soap.

In case of contact with eyes, wash with plenty of potable water for at least 15 minutes and seek medical advice.

If there is any irritation to the skin, eyes or ingestion of the product, seek medical advice, informing the type of product.

If swallowed, do not induce vomiting and seek medical help immediately.

## 9. Environmental Care

Do not dispose of the product or packaging in the environment. Dispose of the material in accordance with current local environmental legislation and applicable regulations according to the characteristics of the product or material.

For more details, consult the safety data sheets of the products mentioned on the website www.viapol.com.br

Note: The information contained in this sheet is based on our knowledge for your help and guidance. We emphasize that the performance of our products depends on surface preparation, application and storage conditions, which are not under our care. Practical performance depends on the application technique, equipment conditions and the surface to be coated. We therefore do not assume any responsibility regarding performance and performance of any nature as a result of improper use of the product. For further information, consult our technical department.

Viapol reserves the right to change the specifications or information contained in this leaflet without prior notice.