

VIT 115

Asphalt Cement

DESCRIPTION

Vit 115 comes from an industrial process, under conditions of predetermined temperature and injection of an air current through a mass composed of Distilled Petroleum Asphalts modified with Special Additives. These elements give the final products softening points and varied penetrations, providing the most diverse uses, for which specific characteristics of adherence, impermeability, binder, insulation and sealing are required.

TECHNICAL CHARACTERISTICS

TECHNICAL CHARACTERISTICS	UNIT	VIT 115
softening point	°C	110 - 120
Penetration (25°C, 100g, 5sec)	mm/10	10 - 20
Heating loss at 163°C/5h	% Pasta	Max. 0.500
flash point	°C	Min. 230
Solubility in trichlorethylene	% Pasta	Min. 99.0

USE

Vit 115 is mainly used as a raw material for the rubber industry, anti-noise putties, bituminous paints, electrical insulators, waterproofing products and special adhesives .

For other uses, consult the Technical Department (sac@viapol.com.br).

PACKING / STACKING

PACKAGING
25kg multi-ply paper bags
I run heated tank with minimum 18ton

VALIDITY / STORAGE

Twenty-four (24) months from the date of manufacture in original packaging, sealed and intact, in a covered, dry, ventilated place and away from heat sources.

SAFETY RECOMMENDATIONS

Before starting work, consult the FISPQ (Safety Data Sheet for Chemical Products), available on our home page www.viapol.com.br .

Use suitable PPE such as gloves and face protection mask, waterproof boots and safety glasses.

Keep the product out of reach of children and pets.

In case of contact with the skin, wash the area with water and neutral soap.

In case of contact with eyes, rinse with plenty of drinking water for at least 15 minutes and seek medical advice.

In case of irritation of the skin, eyes or ingestion of the product, seek medical advice, informing about the type of product.

In case of ingestion, do not induce vomiting and seek medical attention immediately.

ENVIRONMENTAL CARE

Do not dispose of the product or packaging in the environment. Properly dispose of waste in accordance with current legislation on the local environment and applicable regulations in accordance with the characteristics of the product or material . Do not reuse empty packages.

For further details, consult the safety data sheet (MSDS) for **Vit 115** on the website www.viapol.com.br

*“ **Note** : The information contained in this sheet is based on our knowledge for your help and guidance. We point out that the performance of our products depends on the surface preparation, application and storage conditions, which are not under our care. The practical performance depends on the application technique, equipment conditions and the surface to be coated. We do not assume, therefore, any responsibility regarding the yield and performance of any nature as a result of the improper use of the product. This product requires specialized labor for application. For more information, consult our technical department.”*

Viapol reserves the right to change specifications or information contained in this brochure without prior notice.